

4

3

2

1

NOTES UNLESS OTHERWISE SPECIFIED

- PARENT MATERIAL: 304 STAINLESS STEEL, 16 GAUGE (0.060" THICK)
- PART IS SEAMLESS, FORMED FROM SHEET METAL WITHOUT WELDS.
- FINISH: NO METAL FINISHING REQUIRED. THE FINAL FINISH SHALL BE THE RESULT OF THE PROCESSES USED TO FABRICATE THE SHAPE, RESULTING IN AN ESTIMATED SURFACE ROUGHNESS OF 80 Ra.
- PART IS NOT DESIGNED FOR PRESSURE OR VACUUM APPLICATIONS.

Top view of the beaded lid showing concentric circles and a vertical section line A-A.

3D perspective view of the beaded lid.

SCALE 1 : 7

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
00	INITIAL RELEASE FOR MANUFACTURING		
A	Changed OAH from 0.56" to 0.50".	18JUN2014	B.KEEL
B	Updated sheet format, corrected title block and revision block author information, changed Radius from 0.155+/-0.035" to 0.10+/-0.05", changed ID from 15.50" to 15.56", changed OAH from 0.50" to 0.53".	MAR2019	R.DAVIS
C	Added note referencing pressurized lids.	3NOV2023	C. FANKHAUSER

Section A-A and Detail E of the beaded lid. Section A-A shows the profile with dimensions: (Ø 16.15 OD), (Ø 15.56 ID), and a radius of R.10±.05. Detail E shows a close-up of the beaded edge with dimensions: .53, .13, and R.10±.05.

SECTION A-A

DETAIL E
SCALE 2 : 1

UNLESS OTHERWISE SPECIFIED:

- DO NOT SCALE DRAWING
- DIMENSIONS ARE IN INCHES
- TOLERANCE:
 - FRACTIONAL ± .25
 - X.X ±.1
 - X.XX ±.03
 - X.XXX ±.010
 - ANGULAR: ±2 DEG.
- INTERPRET DRAWING PER ASME-Y14.5M-1994 STANDARDS
- THIRD ANGLE PROJECTION
- REMOVE BURRS & BREAK ALL SHARP EDGES WITH R0.03 ±.02

	NAME	DATE
DRAWN	R.DAVIS	MAR2019
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED WITHIN THIS DRAWING IS THE SOLE PROPERTY OF TOLEDO METAL SPINNING COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT WRITTEN PERMISSION OF TOLEDO METAL SPINNING COMPANY IS PROHIBITED.

TOLEDO METAL SPINNING COMPANY EST. 1929		
TITLE: TMS 304SS BEADED LID		
SIZE A	DRAWING NUMBER TMSL1416-BEADED	REV C
SCALE: 1:4	WEIGHT: 3.76	SHEET 1 OF 1