

4

3

2

1

NOTES UNLESS OTHERWISE SPECIFIED

- PARENT MATERIAL: 304 STAINLESS STEEL, 16 GAUGE (0.060" THICK)
- PART IS SEAMLESS, FORMED FROM SHEET METAL WITHOUT WELDS.
- FINISH: NO METAL FINISHING REQUIRED. THE FINAL FINISH SHALL BE THE RESULT OF THE PROCESSES USED TO FABRICATE THE SHAPE, RESULTING IN AN ESTIMATED SURFACE ROUGHNESS OF 80 Ra.
- PART IS NOT DESIGNED FOR PRESSURE OR VACUUM APPLICATIONS.

REVISIONS

REV.	DESCRIPTION	DATE	APPROVED
00	INITIAL RELEASE FOR MANUFACTURING		
A	Updated sheet format, corrected title block and revision block author information, changed Radius from 0.155+/-0.035" to 0.10+/-0.05", changed OAH from 0.31" to 0.53".	MAR2019	R.DAVIS
B	Added note referencing pressurized lids.	3NOV2023	C. FANKHAUSER

Top view of the beaded lid showing concentric circles and a vertical section line A-A.

Section A-A and Detail E of the beaded lid. Section A-A shows the profile with dimensions: outer diameter (ø 10.72 OD), inner diameter (ø 10.13 ID), and a radius of R.10±.05. Detail E shows a close-up of the beaded edge with dimensions: .53 (width of the bead), .13 (width of the groove), and R.10±.05 (radius of the bead).

DETAIL E
SCALE 2 : 1

SECTION A-A

3D perspective view of the beaded lid.

SCALE 1 : 5

UNLESS OTHERWISE SPECIFIED:
 1. DO NOT SCALE DRAWING
 2. DIMENSIONS ARE IN INCHES
 3. TOLERANCE:
 FRACTIONAL ± .25
 X.X ±.1
 X.XX ±.03
 X.XXX ±.010
 ANGULAR: ±2 DEG.
 4. INTERPRET DRAWING PER ASME-Y14.5M-1994 STANDARDS
 5. THIRD ANGLE PROJECTION
 6. REMOVE BURRS & BREAK ALL SHARP EDGES WITH R0.03 ±.02

	NAME	DATE
DRAWN	R.DAVIS	MAR2019
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED WITHIN THIS DRAWING IS THE SOLE PROPERTY OF TOLEDO METAL SPINNING COMPANY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT WRITTEN PERMISSION OF TOLEDO METAL SPINNING COMPANY IS PROHIBITED.

TOLEDO METAL SPINNING COMPANY EST. 1929		
TITLE: TMS 304SS BEADED LID		
SIZE A	DRAWING NUMBER TMSL916-BEADED	REV B
SCALE: 1:3	WEIGHT: 1.72	SHEET 1 OF 1